

A

Abbreviations

- accuracy 1221
- geometric 609–614
- mathematical and signs 2
- scientific and engineering terms 2554–2555
- symbols for mechanics 115
- welding 1396

ABEC bearing tolerances 2256–2261

Abrasive

- belt
 - grinding 1193–1194
 - selecting 1194
- contact wheel
 - selecting 1195
- cubic boron nitride (CBN) 755–757, 1140, 1157, 1166
- cutting 1195–1196
- diamond 1139
- grains and materials 1139
- grinding 1139
- honing 1196–1199
- lapping 1199–1202
- polishing 1440–1441

ABS plastics 380, 579, 588, 601, 2511

Absolute

- programming, NC 1240
- system of measurement 114
- temperature 2514
- zero 2514

Acceleration 114, 151, 153–154

- angular 153
- constant 152
- linear, of point on rotating body 154
- of gravity, g 114

Accuracy

- effect of, on part tolerances 1220
- of NC machine tools 1218–1219
- positioning 1216
- repeatability, and resolution, NC 1216
- significance of 1218–1219

Acetal plastics 380, 579, 588, 597, 601

Acetylene, specific gravity 371

Acme threads

- abbreviations 1795
- ANSI Standard 1792–1816
- centralizing 1802–1811
- checking 1870–1874
- drill sizes for 901

Acme threads

(continued)

- general purpose 1792–1802
- multiple start 1795, 1800
- stub type 1811–1816
- taps for 898–901
- thread profile form 1793–1794
- types of 1792, 1802, 1811
- wire sizes for checking 1872–1874

Acres to hectares 2541

Acrylic plastics 380, 588, 597, 601

Active face width 1998

Active spline length 2127

Actual space width 2127

Actual tooth thickness 2127

Adaptive control, NC 1233

Addendum 1998

- chordal 2017–2018, 2062
- modification 2044
- involute spur and helical gears 2044

Addresses, letter, NC 1243

Adhesives, bonding 2460–2466

- one-component 2461–2463
- retaining compounds 2463–2464
- sealants 2464–2466
- thread-locking 2463–2464
- two-component 2460–2462

Adiabatic expansion and compression 395–401

Adjusting gear blanks for milling 2062

Aerodynamic lubrication 2321

Aging of metal 479

AGMA

- backlash allowance and tolerance
 - fine-pitch spur, helical and herringbone gearing 2041
- recommended backlash range
 - bevel and hypoid gears 2038
 - coarse-pitch spur, helical and herringbone gearing 2037

AGMA Standard

- AGMA 112.05 2001
- AGMA 115.01 2001
- AGMA 116.01 2001
- AGMA 202.03 2054
- AGMA 208.03 2054
- AGMA 209.04 2054
- AGMA 330.01 2054
- AGMA 370.01 2066
- AGMA 390.03 2038
- backlash recommendations 2037–2038, 2041

- Air**
 adiabatic expansion and
 compression 395–396
 compression and flow 393, 396–401
 density 394
 flow in pipes 401
 isothermal expansion and
 compression 396
 power or work to compress 396, 398–400
 pressure, temperature, and volume
 relationships 395
 properties of 393–394
 velocity of escaping 401
 volume and weight at different
 temperatures 393
 volume transmitted through pipes 401
- Airdry wood, weight per cubic foot** 377
- AISI-SAE** 406–408
- Alcohol, specific gravity** 371
- Algebra and equations** 20
- Algebraic**
 expressions and formulas 32
 rearrangement and transposition of
 terms 20–21
- Alignment variation** 2127
- Allowances and tolerances for**
 cylindrical fits, ANSI Standard for 627–
 657
 fits 621–667
 fits, preferred series 628–630
 metric ISO fits, British Standard for 657–
 666
- Allowances for bending sheet metal** 1304–
 1310
- Alloy cast iron** 1330
- Alloy steels** 406
 AISI-SAE designations 409–410
 basic numbering system 403, 405
 carburizing grades 422–423
 castings 1335
 compositions 411–412
 directly hardenable grades 424–425
 effects of alloying elements 2114–2117
 hardness of heat-treated 432–436
 heat treatments 505
 mechanical properties 432–436
 numbering system 403, 405
 quality variations 418
 selection for making tools 452–456
 speeds for drilling and reaming 1030–
 1033, 1035
 speeds for milling 1014–1019
 speeds for turning 996–999
 strength of heat-treated 432–436
- Alloys**
 aluminum 542–557
 bearing 1344, 2238–2242
 brazing 1354–1361
 cast iron 1328–1329
 cast steels 1332–1335
 copper 525–542
- Alloys** *(continued)*
 copper-beryllium 565–566
 copper-silicon 565
 die casting 1342–1344
 magnesium 557–560
 nickel 561–563
 nonferrous 525–566
 nonferrous, strength 477
 numbering systems for 403
 soldering 1352–1355
 titanium 561, 564
- Alternating current motors** 2449–2452
- Alternating stress** 197
- Aluminum**
 alloys 542–557
 Association 543, 546–548
 bearings 2241
 cast
 composition of 546–548, 550–551
 strength of 477
 strength of 550–551
 characteristics of 542–543
 clad 546
 composition of
 wrought 556–557
 designations 546
 die casting 1342–1343
 heat treatability of wrought 546
 machining 1116
 melting point 368–369
 properties of 550–557
 series groups 546–549
 soldering 1352–1354
 structural shapes 2498
 temper designation 543–546
 welding 1365, 1386–1387, 1390
 wrought 477, 546–557
- Aluminum bronze**
 casting alloy 532
 strength 477
 cast 550–551
- American**
 Boiler Makers Association 268
 Brass Company 565
 Bureau of Shipping 355, 1335
 Foundrymen's Association 479
 Gear Manufacturers Association
 (AGMA) 2001, 2004, 2037–2038,
 2041
 Institute of Steel Construction 265
 column formulas 267
 Iron and Steel Institute (AISI) 360, 403,
 405
 Steel Products Manual 411–412
 Wire and Rods, Carbon Steel 435
 National fire hose connection
 threads 1842–1845
 Railroads, Assn. of 1335
 Screw threads, wire sizes for
 measuring 1861–1862
 Society for Metals (ASM) 479, 521

- American *(continued)*
- Society for Testing and Materials
 - (ASTM) 479, 520–521, 557–560, 1328–1331, 1335
 - annealing temperatures 496–497
 - copper alloys 525–542
 - Standard Code for Information Interchange (ASCII) 1295
 - wire gage 2499–2500
- American Standard B1.1 1712
- Ammonia, specific gravity 371
- in nitriding 417
- Amortization 27
- AMS 2404C 1447
- AMS 2405B 1447
- AMS 2433B 1447
- Analysis, break-even 40–42
- Angles
- bent to circular shape, lengths of 2488
 - between lines tangent to two circles 685
 - compound 688–690
 - cutting tool 723–730
 - cutting tool inserts 1281–1284
 - degrees into radians 90, 92
 - functions of 83–101
 - helix 1933
 - indexing 1950–1993
 - involute functions of 97–101
 - lead 1933
 - length of arc of given radius 80–81
 - length of chord 80–81
 - measuring by disc method 682–683
 - minutes into decimals of a degree 90, 92
 - moment of inertia 2495–2497
 - radius of gyration 2495–2497
 - section modulus 2495–2497
 - sine bar for measuring 673–682
 - structural 2495–2497
 - taper per foot corresponding to 684
 - rules for figuring 682–683
 - thread, tolerances on gages 1882
 - to find, for given taper per foot 682–685
 - useful relationships among 93
 - weight per foot 2495–2497
- Angular
- acceleration 153
 - torque, relation to 156
 - backlash in gears 2042
 - clearance for dies 1302
 - indexing 1956–1977
 - velocity 151–153, 187
 - of rotating bodies 187
- Annealing 414–415, 479, 495
- constant temperature, transformation 496–497
 - double 496
 - temperatures 496
- Annual cost method 27–29
- Annuities (calculation of) 26–27
- Anode 1319
- Anodizing 1444
- Anodizing *(continued)*
- hard 1448
 - ANSI / RMA IP-26, 1977 2398
 - ANSI B1.20.5 1854
 - ANSI B1.1 1506, 1508, 1712
 - ANSI B1.12 1786
 - ANSI B1.13M 1538, 1544, 1762
 - ANSI B1.18M 1755
 - ANSI B1.20 1848
 - ANSI B1.20.1 1848, 1851
 - ANSI B1.20.3 880, 1853–1854
 - ANSI B1.3 1879
 - ANSI B1.3M 1774
 - ANSI B1.5 1792, 1811
 - ANSI B1.9 1818, 1822–1823, 1877
 - ANSI B17.1 2342–2343, 2345–2347
 - ANSI B17.2 2348–2350
 - ANSI B18.1.1 1464, 1468–1470
 - ANSI B18.1.2 1464–1467
 - ANSI B18.16.1M 1542, 1547
 - ANSI B18.16.3M 1520, 1542, 1547
 - ANSI B18.17 1693–1701
 - ANSI B18.2.1 1492
 - ANSI B18.2.2 1492, 1510
 - ANSI B18.2.3.1M 1520–1521
 - ANSI B18.2.3.2M 1520, 1522, 1524
 - ANSI B18.2.3.3M 1520, 1523
 - ANSI B18.2.3.4M 1524
 - ANSI B18.2.3.5M 1520, 1524, 1530
 - ANSI B18.2.3.6M 1520, 1524, 1529
 - ANSI B18.2.3.7M 1520, 1528–1529
 - ANSI B18.2.3.8M 1520, 1525, 1532
 - ANSI B18.2.3.9M 1524
 - ANSI B18.2.4.1M 1520, 1542–1543
 - ANSI B18.2.4.2M 1520, 1542–1543
 - ANSI B18.2.4.3M 1520, 1542
 - ANSI B18.2.4.4M 1520, 1542, 1544–1545
 - ANSI B18.2.4.5M 1542, 1548
 - ANSI B18.2.4.6M 1520, 1542, 1548
 - ANSI B18.22.1 1512–1513, 1515
 - ANSI B18.22M 1520, 1549
 - ANSI B18.3 1541
 - ANSI B18.3.1M 1522
 - ANSI B18.6.1 1456
 - ANSI B18.6.3 1568–1577
 - ANSI B18.6.4 1620, 1622–1625, 1627, 1635
 - ANSI B18.6.7M 1568
 - ANSI B18.8.1 1649
 - ANSI B212.1 738–739, 741–746, 859–860, 862–864
 - ANSI B212.12 730
 - ANSI B212.4 731
 - ANSI B212.5 733–734
 - ANSI B27.7M 1665–1668, 1670, 1672–1673
 - ANSI B29.1M 2435
 - ANSI B32.1 2501
 - ANSI B32.4M 644
 - ANSI B4.1 627, 630, 634, 636, 638–640, 2267–2268
 - ANSI B4.2 642, 644, 646, 648–655, 657

- ANSI B4.4M 656
 ANSI B47.1 1882
 ANSI B5.18 920, 922–924
 ANSI B6. 7 2024
 ANSI B6.1 2004–2006, 2008–2009, 2011, 2019, 2023
 ANSI B6.7 2008, 2011, 2023–2026, 2079
 ANSI B6.9 2064–2065
 ANSI B7.1 1170, 1174, 1196
 ANSI B7.1-1988 1173
 ANSI B74.13 1141, 1166
 ANSI B74.2 1142–1143, 1148, 1150, 1204–1206
 ANSI B74.3 1163–1165, 1167
 ANSI B92.1 2130–2131, 2133–2134, 2137, 2139, 2149–2150
 ANSI B92.2M 2126, 2148–2150
 ANSI B94.11M 827, 837
 ANSI B94.2 813–820, 822–826
 ANSI B94.25 731
 ANSI B94.33 942–943, 945–950
 ANSI B94.35 848, 850
 ANSI Standard
 abbreviations 115, 2554–2555
 Acme threads 1792–1816
 bolts, nuts, screws, and washers, inch 1492–1519
 bolts, screws, and nuts, metric 1520–1524, 1548–1549
 boring tools, carbide 859–864
 buttress inch type threads 1818–1824
 cap screws, hex head 1496, 1520
 cap screws, metric 1520–1523
 castle and slotted nuts 1500–1502
 chain, transmission 2421–2426
 Class 5 threads 1786–1788
 cutting tools 730–746
 diamond wheels 1163–1168
 drafting practices 606
 drafting room practice 606–611
 drill drivers 848–850
 drive screws 1635
 electric socket and lamp base threads 1846
 engineering drawings 606
 fine pitch standard gear tooth parts 2009
 fine-pitch
 helical gears 2077–2080
 worm gearing 2064–2066
 fine-pitch worm gearing
 ANSI B6.9 2064
 flat metal products
 inch sizes 2501–2502
 metric sizes 2503
 gage usage, recommended 656
 gagemakers
 tolerances 656
 gages 1876–1884
 for self-holding tapers 914
 for Unified screw threads 1877–1884
 gear tooth forms 2004–2010
- ANSI Standard *(continued)*
 geometric characteristic symbols for engineering drawings 609–614
 geometric dimensioning and tolerancing 606–611
 grinding wheel safety 1170–1174
 grinding wheels 1141–1149, 1157, 1166
 hexagon socket head shoulder screws 1605
 hose coupling screw threads 1841–1845
 interference-fit threads 1786–1791
 involute spline symbols 2130
 involute splines
 inch dimensions 2126–2147
 metric module 2148–2155
 jig bushings 941–951
 key drive 911–912
 keys and keyseats 2342–2354
 keys and keyways for milling cutters and arbors 794
 knurls and knurling 1211–1215
 letter symbols for mechanics 115
 limits and fits 627–657
 lock washers 1515–1519
 machine screws 1568–1577
 binding head 1576
 fillister head 1574
 flat, countersunk head 1569–1571
 hexagon washer head 1571
 metric 1578–1585
 oval head 1574–1576
 pan head 1573
 round head 1577
 slotted hexagon 1572
 truss head 1572
 manufacturers' standard gage for sheet steel 2501–2502
 metric
 cap screws 1520–1523
 retaining rings 1666–1673
 screw threads, M profile 1755–1776
 screw threads, MJ profile 1777–1780
 screws, bolts, nuts, and washers 1520–1525, 1533–1534, 1546–1549
 microscope threads 1846
 milling cutters 772–795
 miniature threads 1781–1785
 numerical control 1226
 nuts 1492–1504
 nuts, metric 1541, 1543–1548
 pins 1648–1664
 pipe and pipe fittings 2504–2508
 pipe thread 1846–1855
 plain washers 1512–1517
 position symbols 1221
 preferred
 basic sizes 644
 fits 644–647
 metric limits and fits 632, 642–657
 metric sizes 642–644
 numbers 19

- ANSI Standard *(continued)*
- thicknesses, thin, flat metals 2501
 - reamers 813–815, 820–826
 - retaining rings 1666–1673
 - rivets 1464–1470
 - roundness symbols 1222
 - runout symbols 1224
 - screw thread symbols 1787, 1793–1794, 1811, 1816, 1824
 - metric 1756–1778
 - screw threads 1706–1710, 1712–1790, 1793–1816, 1818–1824
 - metric M profile 1755–1776
 - metric MJ profile 1777–1780
 - screws and bolts
 - inch 1492–1509
 - metric 1520–1527, 1529, 1532–1534, 1541
 - section lining symbols 606, 608
 - self-tapping thread inserts 1635
 - self-threading screws, inch 1620–1635
 - metric 1635–1644
 - serrations, involute 2126
 - set-screw heads and points 1606–1610
 - set-screws, socket type 1607, 1612
 - shoulder screws 1605
 - single-point tools and tool posts 740–746
 - slotted head cap screws 1599–1600
 - slotted headless set screws 1606
 - socket head cap screws 1601–1605
 - spindles and drives for portable tools 1207–1210
 - spline socket set screws 1607, 1612
 - splines, involute
 - inch dimensions 2126–2147
 - metric module 2148–2155
 - spur gear tooth forms 2004–2010
 - stub threads, 29- and 60-degree 1811–1816
 - stud threads 1786–1791
 - studs, drive 1659, 1662
 - surface texture 697–708
 - symbols
 - accuracy 1221
 - accuracy symbols 1221
 - comparison to ISO 609
 - concentricity 609, 1223
 - datum referencing 614
 - diameter 609, 1222
 - drawing practices for surface texture 704–708
 - parallelism 609
 - part tolerance 609, 642–644
 - perpendicularity 609
 - position 609
 - roundness 609
 - runout 609
 - section lining 606, 608
 - total runout 609
 - welding 1393
 - symbols for section lining 608
- ANSI Standard *(continued)*
- tang drives 909–910
 - tapers 906–918
 - taps and threading dies 872–898
 - threads for electric sockets 1846
 - T-nuts, T-bolts, T-slots 1645–1647
 - tolerances 630
 - gagemakers 656
 - symbols 578–579, 609–614, 622
 - tolerances and allowances for cylindrical fits 621–657
 - tooth proportions, fine-pitch involute spur and helical gears 2008
 - total runout symbols 1224
 - twist drills 827–849
 - Unified threads 1706–1710, 1712–1754, 1781–1786
 - washers, inch 1512–1519
 - metric 1547, 1549
 - welded and seamless wrought steel pipe 2505
 - wing nuts, wing screws, and thumb screws 1693–1701
 - wood screws 1456
 - woodruff keys 2348–2354
 - worm gearing, fine pitch 2064–2066
 - wrench openings 1510–1511
- ANSI Standard Z17.1-1973 19
- ANSI X3.37 1264
 - ANSI Y10.4 115
 - ANSI Y14.1 606
 - ANSI Y14.2 1294
 - ANSI Y14.2M 608
 - ANSI Y14.36 606
 - ANSI Y14.5M 1286
 - ANSI Z136.1 1413
 - ANSI 14.5M 1221
 - ANSI, RMA IP-25 2402
 - ANSI/AFBMA Std 10 2303, 2306
 - ANSI/AFBMA Std 11 2291
 - ANSI/AFBMA Std 11–1978 2297
 - ANSI/AFBMA Std 18.1 2263, 2270–2271
 - ANSI/AFBMA Std 18.2 2263–2264, 2269–2271
 - ANSI/AFBMA Std 20 2256–2257
 - ANSI/AFBMA Std 20, 1987 2258–2260
 - ANSI/AFBMA Std 24.1–1989 2261
 - ANSI/AFBMA Std 24.2 2262
 - ANSI/AFBMA Std 24.2–1989 2261
 - ANSI/AFBMA Std 7 2265, 2267–2268
 - ANSI/AFBMA Std 8.2 2276–2279
 - ANSI/AFBMA Std 9 2286, 2297
 - ANSI/AGMA 2005 2054
 - ANSI/AMSE B18.16.3M 1546
 - ANSI/ASME B1.1 1712
 - ANSI/ASME B1.12 1788–1791
 - ANSI/ASME B1.13M 1755, 1757–1759, 1763–1764, 1766–1768, 1774, 1776
 - ANSI/ASME B1.2 1864, 1877, 1880, 1883–1884
 - ANSI/ASME B1.20.1 1847–1851

- ANSI/ASME B1.20.7 1841–1842
 ANSI/ASME B1.21M 1755, 1777
 ANSI/ASME B1.3M 1712, 1791
 ANSI/ASME B1.7M 1707, 1712
 ANSI/ASME B18.1.3M 1464
 ANSI/ASME B18.2.1 1492–1498, 1551
 ANSI/ASME B18.2.2 1492–1493, 1499–1502, 1510, 1551
 ANSI/ASME B18.2.3.4M 1527
 ANSI/ASME B18.2.3.5M 1530
 ANSI/ASME B18.2.3.9M 1526–1527
 ANSI/ASME B18.21.1 1515–1519
 ANSI/ASME B18.21.2M 1515
 ANSI/ASME B18.3 1601–1605, 1607–1608, 1611–1613
 ANSI/ASME B18.3.1M 1532, 1539, 1541
 ANSI/ASME B18.5 1505–1509
 ANSI/ASME B18.5.2.2M 1527–1528, 1531
 ANSI/ASME B18.6.2 1599–1600, 1606, 1609–1610
 ANSI/ASME B18.6.5M 1623, 1635–1640
 ANSI/ASME B18.6.7M 1577–1585
 ANSI/ASME B18.8.2 1651–1655, 1658–1664
 ANSI/ASME B29.1 M 2421
 ANSI/ASME B29.1M 2421–2422, 2425–2429, 2438, 2442
 ANSI/ASME B29.3M 2422
 ANSI/ASME B32.3M 2503
 ANSI/ASME B36.10M 2504–2505
 ANSI/ASME B5.1M 1645–1647
 ANSI/ASME B5.10 848, 909–914, 918
 ANSI/ASME B5.15 2156
 ANSI/ASME B5.50 1284–1286
 ANSI/ASME B92.2M 2156
 ANSI/ASME B94.11M 829, 839–841, 846–847, 849
 ANSI/ASME B94.19 772–795
 ANSI/ASME B94.6 1211, 1213–1214
 ANSI/ASME B94.9 872
 ANSI/ASME Y10.3M 115
 ANSI/ASME Y14.2M 607
 ANSI/AWS A2.4 1396
 ANSI/AWS 2.4-79 1408
 ANSI/EIA RS 274-D 1227, 1240–1241, 1243, 1245, 1248–1249, 1264
 ANSI/RMA IP-20 2379–2381
 ANSI/RMA IP-21 2386
 ANSI/RMA IP-22 2373–2375, 2377
 ANSI/RMA IP-23 2394–2396
 ANSI/RMA IP-24 2409, 2411–2414
 ANSI/RMA IP-25 2402–2403
 ANSI/RMA IP-26 2397, 2400
 ANSI/RMP IP-21 2387
 ANSI/RMP IP-24 2411
 ANSI/SAE AS568A 2482
 Antifriction bearings 2246–2302
 Apothecaries'
 fluid measure 2518
 weight 2519
 Application factor 2044–2045
 Applying surface texture symbols 706
 APT (automatically programmed tool) 1263–1280
 axis nomenclature 1235
 circles 1265–1270, 1272
 computational statements 1265
 example program 1277
 for turning 1279–1280
 geometry statements 1265
 geometry, 3-D 1274
 motion statements 1270–1275
 planes 1273
 points 1266
 postprocessor statements 1275–1280
 programming 1263–1280
 tabulated cylinder 1274
 Arbors
 circular saw 1203
 diameters for spring-winding 332
 dimensions of centers 813
 driving slots and lugs for shell reamer 823
 keys and keyways for 794
 lathe 858
 shell reamer 823
 standard milling machine 920–924
 steels for 456
 Arbor-type milling cutters 790
 Arc
 checking radius of 690–692
 electric, cutting of metals 1391, 1428–1429
 length of given angle and radius 80–81
 of action 1998
 of approach 1998
 of recession 1998
 plasma welding 1387–1391
 thickness of internal gear tooth 2047
 thickness of pinion tooth 2047
 welding 1362–1387
 Arc of recession 1998
 Area
 circle 63
 circular
 ring 64
 ring sector 64
 sector 63
 segments 63, 78, 80–81
 cycloid 63
 different sections 217–227
 ellipse 65
 enclosed by cycloidal curve 58
 fillet 64
 finding by Simpson's rule 57–58
 geometrical figures 60–65
 hexagon 62
 hyperbola 65
 irregular outline 57–58
 octagon 62
 parabola 64–65
 segment of 65

- Area *(continued)*
- parallelogram 60
 - plane figures 60–65
 - plane surface of irregular outline 57–58
 - polygon 62
 - rectangle 60
 - spandrel 64
 - square 60
 - surface of revolution 56–57
 - trapezium 62
 - trapezoid 61
 - triangle 61
- Areas and volumes 56–59
- Argon, welding gas 1364–1366, 1374, 1387–1388
- Arithmetical
- operations, sequence of 21
 - progressions 43–44
- ASA B1.10 1902
- ASA B1.12 1559
- ASA B17c 281
- ASA B18.2 1492, 1510
- ASA B5.38 1207–1210
- ASA B6.1 2005, 2009–2010
- ASA Code for transmission shafting 280
- Asbestos, specific gravity and weight 370
- ASCII, American Standard Code for Information Interchange 1295
- ASME Y14.5M 609
- ASME/ANSI B 1.8 1800
- ASME/ANSI B1.5 1807
- ASME/ANSI B1.1 1739, 1753–1754
- ASME/ANSI B1.12 1786
- ASME/ANSI B1.3M 1753
- ASME/ANSI B1.5 902, 1792–1794, 1796, 1799–1805, 1808–1811
- ASME/ANSI B1.8 1793, 1801, 1811–1813, 1815
- ASME/ANSI B29.1M 2423, 2443
- ASME/ANSI B94.9 872, 876–895, 897–898
- ASTM A 220 1331
- ASTM A297 1334
- ASTM A307 1488, 1495
- ASTM A325 1488
- ASTM A325M 1530
- ASTM A354 1488, 1496
- ASTM A449 1488, 1496
- ASTM A490 1488
- ASTM A490M 1530
- ASTM A563M 1542, 1544, 1547
- ASTM A574M 1531
- ASTM A743-81a 1335
- ASTM B23-83 2239
- ASTM B253 1447
- ASTM B438-83a 2243–2245
- ASTM B439-83 2243, 2245
- ASTM B633 1451
- ASTM E-140 2306
- ASTM E-18 2306
- ASTM F467M 1544
- ASTM F568 1530
- ASTM F594 1494
- ASTM F837M 1531
- ASTM 574M 1530
- Atmospheric pressure 393, 2519
- Austempering 479, 491–492
- Austenite 483–484, 514
- Austenitic manganese cast steel 1335
- Autocollimation 1219–1220
- Autogenous, (welding) 1362
- Automatic screw machines 1094–1099
- knurling on 1094
- Avoidupois or commercial weight 2518
- Axial
- pitch 1998
 - plane 1998
 - thickness 1999
- Azimuth reading displacements 1219
-
- ## B
- B & S automatic screw machines 1094
- Babbitt metals 2238–2242
- properties of 2240–2242
 - SAE general information 2238
- Backlash 1999
- allowance in checking gears by the pin method 2103
 - control of allowances in production 2039
 - control of in assemblies 2041
 - determining proper amount of 2036
 - fine-pitch gears 2040
 - gearing 2036–2042
 - recommended 2038
- Bainite 481
- Balance wheels 173
- Balancing
- calculations 167–172
 - counterbalancing masses located in two or more planes 170–171
 - counterbalancing several masses located in single plane 168–170
 - dynamic 167
 - lathe fixtures 171–172
 - machines 167
 - rotating parts 167–172
 - running or dynamic 167
 - static 167
- Ball bearings 2246–2252, 2254–2261, 2264–2266, 2271–2301
- alignment and squareness 2273–2274
 - allowance for axial displacement in 2264
 - angular contact 2246–2248
 - cage materials 2254–2255
 - clamping and retaining methods 2274–2280
 - clearances, running 2282–2284
 - closures 2275, 2280
 - design and installation 2264
 - designation of 2267
 - failures 2285

- Ball bearings (continued)
- fits 2275, 2280
 - flanged housing 2254
 - friction losses 2280
 - handling precautions 2284–2285
 - housing bore tolerances 2267–2268
 - housings, soft metal and other 2274–2275
 - life 2285
 - life adjustment factors 2296
 - locknuts and shafts for 2277–2278
 - lockwashers for 2276
 - lubricants 2318–2320
 - lubrication 2282
 - materials for 2254
 - mounting 2271–2284
 - pillow block 2254
 - plastics 2254
 - quiet or vibration-free mountings 2275
 - radial and axial clearance 2283–2284
 - rating life 2287–2291
 - seating fits for 2275
 - selection 2281–2283
 - shaft
 - and bore limits 2267–2268
 - and housing fits for metric radial 2264–2266
 - tolerance
 - classifications, metric 2265–2266
 - limits, metric 2266–2267
 - special or unconventional types of 2254
 - squareness and alignment 2273–2274
 - starting torque 2281
 - static
 - equivalent loads 2300–2301
 - load ratings 2297–2300
 - thrust 2250
 - tolerances 2255–2261
 - types of 2246–2254
- Ball, roller, and needle bearings 2246–2302
- Balls, standard 2302–2310
- grades 2305
 - hardness corrections 2306
 - hardness ranges 2306
 - materials 2305
 - number per kilogram 2310
 - number per pound 2309
 - ordering specifications 2303
 - package markings 2293–2294
 - preferred gages 2303
 - preferred sizes 2306–2308
 - tolerances 2305–2306
- Band brakes 2337–2339
- Band saw
- blade selection 1101–1102
 - break-in 1105–1106
 - speeds and feeds, metal cutting 1103–1105
- Bar, small diameter radius of gyration 147
- Barometer reading and equivalent pressure 395
- Barrel
- liquid capacity 2518
 - volume 71
- Barrel effect 1319
- Base
- circle 1999, 2127
 - diameter 2127
 - helix angle 1999
 - pitch 1999
 - tooth thickness 1999
- Base circle 1999
- Base circle, spur gear
- diameter 2004
- Base helix angle 1999
- Base oils for metal cutting 1109
- Base pitch 1999
- Base tooth thickness 1999
- Basic
- endurance limit 2044
 - gear dimensions 2010
 - rack profiles 2153
 - space width 2127
- Basic dimension 621
- hole 621
 - shaft or hole 621
- Baths, hardening or quenching 488–490
- for heating steel 487
 - tanks for 490–491
- Baumé's hydrometer 372
- conversion to specific gravity 371
- Beams 239, 241–242, 248–249, 251–259, 2488–2494
- channel 2494, 2498
 - combined stresses in 206–210
 - curved 254–257
 - deflections 236, 239, 241–242, 253–254
 - designing for 253–254
 - fixed at
 - both ends 252
 - one end 241–242, 249, 251
 - formulas 207
 - I-beams 2488–2493, 2498
 - reactions 236
 - rectangular solid 249
 - simple stresses in 204–205
 - stresses in 204–210, 236, 239, 241–242, 248, 252–258
 - stresses produced by shocks 257–258
 - supported at both ends 239, 249
 - uniform strength 248, 251–252
- Bearing lubricants
- ball and roller bearings 2318–2320
 - plain bearings 2202–2205
- Bearing materials, plain 2236–2244
- aluminum 2238, 2241
 - ASTM compositions 2239–2245
 - babbitt metals 2238–2242
 - cadmium alloys 2240–2242
 - carbon-graphite 2241–2245
 - cast iron 2241
 - copper-lead 2238–2242

- Bearing materials, plain (continued)
- die casting in place 1344
 - graphitic 2242, 2245
 - laminated phenolics 2242
 - leaded bronze 2240–2242
 - nylon 2242
 - oil impregnated 2242–2245
 - plastics laminates 2242
 - porous 2241–2245
 - properties 2236–2237
 - rubber 2242, 2245
 - SAE compositions 2238–2239
 - seals 2198–2199
 - silver 2241
 - Teflon (TFE) 2242, 2245
 - tin-bronze 2240–2242
 - white metal 2238–2242
 - wood 2242, 2245
- Bearing spacing and shaft stiffness 2053
- Bearings 2193–2218, 2220–2244, 2246–2300
- guide 2236–2237
- Belleville springs or washers 326
- Belts and pulleys 2368–2420
- flat belts 2368–2371
 - V-belts 2372–2420
- Bending
- allowances, sheet metal 1304–1310
 - formulas
 - for beams 239, 241–242, 249, 251–257
 - for shafts 275–277
 - stress in beams 236, 239, 241–242, 248–249, 251–254
 - structural angles 2495–2497
- Bending load wood 375
- Beryllium and copper alloys 566
- Bevel gearing 2050–2063
- ANSI/AGMA Standard 2054
 - applications 2051–2053
 - applications of 2051
 - backlash 2037–2038
 - bearing spacing 2053
 - blank design 2052–2053
 - cutting teeth in 2053–2062
 - face angles 2054, 2056–2057
 - face widths 2054, 2056–2057
 - German standard tooth form 2090
 - Gleason system, straight bevel gears 2054
 - Zerol bevel gears 2050–2051
 - hypoid gears 2051
 - materials for 2063
 - milled 2054, 2056–2062
 - milling cutters for 792, 2058–2060
 - milling setup 2061–2062
 - mountings 2052–2053
 - nomenclature 2054–2056
 - octoid tooth form 2053
 - planetary 2083, 2087
 - replacement gear dimensions 2122–2125
 - selecting formed cutters for 2060
- Bevel gearing (continued)
- shaft stiffness 2053
 - spiral 2050
 - straight 1998, 2050, 2052, 2054
 - tooth measurement for milled 2062
 - types of 2050
 - typical steels used for 2063
 - Zerol 1998, 2050–2052
- Bilateral and unilateral tolerances 621–622
- Binary multiples 2533
- Birmingham wire gage 2499–2500
- Birnie's equation 272
- Blank diameters, drawing dies 1302–1307
- Blanks, sintered carbide 738–740
- Blast cleaning of castings 1338
- Block
- brakes 2340
 - NC 1241, 1243, 1245
 - or multiple indexing 1990–1991
- Blow, force of 159–160
- Boilers, strength of flat stayed surfaces 268
- Boiling temperature, various substances 364
- Bolt head
- markings, inch 1484–1488
 - metric 1532, 1534, 1560–1561
 - wrench and socket clearances 1510–1511
- Bolt hole circles
- chordal distance 78
 - coordinates for 953–970
- Bolts and nuts
- ANSI, inch dimensions
 - cap or acorn nuts 1503
 - countersunk bolts 1508–1509
 - fin neck bolts 1506
 - flat jam nuts 1500
 - heavy hex bolts 1495
 - heavy hex structural bolts 1493–1494
 - hex
 - bolts 1493
 - flat nuts 1500
 - high nuts 1504
 - nuts 1493–1494, 1499
 - slotted high nuts 1504
 - slotted nuts 1500–1502
 - thick slotted nuts 1501–1502
 - jam nuts 1499
 - machine screw nuts 1568
 - ribbed neck bolts 1507
 - round head bolts 1505–1507
 - square
 - bolts 1492–1494
 - neck bolts 1505–1508
 - nuts 1492–1493, 1502
 - step bolts 1508
 - T-bolts 1646
 - T-head bolts 1505
 - T-nuts 1647
 - types of 1492–1493
 - Unified 1489–1490, 1492–1496, 1499–1502
 - wing nuts 1693–1697

- Bolts and nuts** (continued)
- ANSI, metric dimensions
 - clearance holes 1532
 - designation 1532
 - diameters 1523
 - heavy hex
 - bolts 1529
 - nuts 1548
 - structural bolts 1529
 - hex
 - flange nuts 1545
 - jam nuts 1548
 - hex nuts 1543
 - identification symbols 1532
 - materials and mechanical properties 1534
 - prevailing torque hex flange nuts 1547
 - nuts 1546
 - reduced diameter bolts 1524, 1527
 - slotted hex nuts 1544
 - thread series 1532
 - British Standard
 - Fine thread 1552–1559, 1619, 1838–1840
 - hexagon 1551–1554
 - metric hexagon 1555–1561
 - standard thread 1839
 - Unified 1597
 - Whitworth 1551–1554, 1591, 1595–1598, 1619, 1836–1838, 1868
 - eye bolts and nuts 358–359
 - grade markings for steel 1484–1488, 1532, 1534, 1541, 1560–1561
 - load allowable on bolts 1489–1491
 - spacing for wrench clearances 1510–1511
 - tightening 1475
 - torque required to tighten 1475–1488
 - working strength of bolts 1489–1491, 1559–1560
 - wrench clearances for 1510
 - wrench openings 1510
- Bolts and screws** 1492
- Bonding, adhesives** 2460
- Boring**
- carbide tools for 859–864
 - cutting time for 1044
 - wood 378
- Boring-bar, cutters, carbide** 859–864
- Boron nitride**
- cubic (CBN) abrasive 982, 1140, 1157, 1166
 - cutting tool materials 982
 - speeds and feeds for 1002, 1008, 1018–1022
- Bottom land** 1999
- Box wrench clearances** 1510
- Brads and wire nails** 1455
- Brakes**
- band 2337–2339
 - block type 2340
 - coefficient of friction 2338–2340
- Brass**
- castings 525–532
 - coloring 1441–1442
 - strength and physical properties 477
 - wire, strength 477
 - EDM 1328–1329
- Brazing** 1354–1361
- filler metals for 1354–1359
 - fluxes for 1354–1359
 - heating for 1360
 - symbols 1361
 - workholders for 1360
- Break-even analysis** 40–42
- Bricks**
- specific gravity and weight 370
 - strength 478
- Briggs (now ANSI) standard pipe thread** 1849–1850
- Brinell hardness** 473, 475, 516–524
- aluminum alloys 550–555
 - cold-drawn carbon steel rounds, squares, and hexagons 395–396
 - heat-treated steels 432–436
 - magnesium alloys 560
 - Rockwell conversion tables 520
 - stainless steels 439
- British Association**
- standard screw threads 1839
 - tolerance formulas 1839
- British Standard**
- BS 1083 1551, 1553–1554
 - BS 1157 1838, 1903–1904
 - BS 1387 1857
 - BS 1449B 1565
 - BS 1580 1551
 - BS 1657 1825
 - BS 1768 1492, 1551
 - BS 1769 1492, 1551
 - BS 1807 2043
 - BS 1916 1650
 - BS 1981 1595, 1597
 - BS 2059 2156
 - BS 21 1856–1858
 - BS 235 2043
 - BS 2519 2043
 - BS 2693 1551, 1559, 1562
 - BS 2708 1551
 - BS 275 1464, 1471
 - BS 2779 1856–1857
 - BS 2827 1586
 - BS 2870 1565
 - BS 2963 1559
 - BS 3027 2043
 - BS 308 2043
 - BS 328 848, 850–856
 - BS 3382 1559, 1586
 - BS 3550 2156

- British Standard *(continued)*
- BS 3643 902, 904, 1560, 1587, 1826, 1831, 1834
 - BS 3692 1551, 1555–1559, 1904–1905
 - BS 3696 2043
 - BS 4084 1825
 - BS 4168 1613–1618, 1904–1905
 - BS 4183 1586, 1588–1589, 1592–1594, 1904–1905
 - BS 4186 1904
 - BS 4190 1551, 1904
 - BS 4235 2354–2355, 2357–2360
 - BS 4320 1565–1567
 - BS 436 2042–2045
 - BS 4464 1563–1565
 - BS 45 1840
 - BS 450 1586, 1595, 1598
 - BS 4500 657, 660–663, 665–666, 2356
 - BS 46 2359, 2361–2364, 2367
 - BS 4620 1473–1474
 - BS 545 2043
 - BS 57 1586
 - BS 6 2365
 - BS 6104 1613
 - BS 6105 1613
 - BS 6186 2156
 - BS 641 1472
 - BS 721 2043
 - BS 821 2043
 - BS 84 1551, 1838
 - BS 93 1551, 1839
 - BS 949 902–903
 - BS 970 2354
 - BS 978 2043
 - clearance holes for metric bolts and screws 1903–1904
 - combined drills and countersinks 847
 - countersunk head screws 1591–1598
 - dowel pins, metric 1648–1650
 - drills, metric 850–856
 - fasteners, mechanical properties 1559–1560, 1613
 - Fine threads (BSF)
 - basic dimensions 1838
 - tolerance formulas 1836
 - hexagon bolts 1551–1554
 - hexagon socket screws, metric 1613–1618
 - button head 1617
 - cap 1614–1615
 - set 1616–1618
 - Imperial wire gauge 2499–2500
 - interference fits 1551, 1562
 - ISO metric
 - grade markings 1559–1560
 - hexagon bolts, screws, and nuts 1555–1561
 - limits and fits 657–666
 - tapping drill sizes for 1903
 - taps 902–903
 - threads 1825–1834
- British Standard *(continued)*
- keys and keyways 2354–2367
 - limits and fits for holes and shafts 657–666
 - machine screws 1586–1598
 - metric
 - and inch pipe threads 1856–1858
 - basic sizes, preferred 667
 - bolts, clearance holes 1903–1904
 - comparison of British, French, German and Swiss 1780
 - dowel pins 1648–1650
 - drills 850–856
 - hexagon socket screws 1613–1618
 - keys and keyways 2354–2367
 - limits and fits 657–666
 - machine screws and nuts 1586–1595
 - series plain washers 1565–1566
 - series spring washers 1563–1565
 - taps, ISO 902–903
 - threads 1780
 - nuts 1552–1555, 1557–1559, 1586–1597
 - PD 3376 2043
 - PD 6457 2044
 - pipe threads, parallel 1856–1857
 - pipe threads, taper 1857–1858
 - preferred metric basic sizes 667
 - preferred numbers 667
 - rivets 1464, 1471–1474
 - screws 1551–1560, 1586–1598, 1613–1619
 - thread dimensions 1825–1858
 - thread profiles 1825, 1836
 - spark plugs 1840
 - spur and helical gears 2042
 - straight splines 2156
 - studs 1551, 1562
 - tapping drill sizes, ISO metric threads 1901–1903
 - taps, ISO, metric 902–903
 - thermal units, (BTU) 2514
 - converted into foot-pounds 2553
 - power and heat equivalents 2551
 - Unified
 - machine screws and nuts 1595–1597
 - screws and nuts 1595–1597
 - thread sizes 1706–1710, 1712–1754, 1781–1785
 - UNJ profile threads 1825–1826
 - washers, plain, metric 1565–1567
 - Whitworth threads (BSW)
 - machine screws 1595–1598
 - set-screws 1595–1598, 1619
 - thread form 1836–1837
 - tolerance formulas 1836
- Broaches
- chip breakers 930–931
 - clearance angles for teeth 930
 - depth of cut per tooth 929
 - depth of teeth 930
 - face angle or rake 930

Broaches *(continued)*
 land width 930
 pitch of teeth 927–930
 radius of tooth fillet 930
 shear angle 930–931
 surface 928
 total length of 930
 types 926–927

Broaching 926–932
 cutting oils for 1108–1109
 cutting speeds for 1043
 difficulties 932
 pressure 928
 types of machines 930–931

Broken tap, removal of 1905–1908

Bronze 525
 castings, strength 477
 strength 477

Brown & Sharpe
 automatic screw machines 1094–1099
 milling machines 1979
 taper 906, 915–916
 taper reamers for sockets 825
 wire gage 2499–2500

Brush finishing, power 1435–1438

Buckingham formula for pin method of
 checking screw threads 1867–1870

Buckling, columns 261–262

Buffing and polishing 1439–1440
 wheels for 1440

Built-up Sections, Moments of Inertia 217

Bulk modulus of various material 384

Bulk temperature thermal flash factor 2045

Burs and files, rotary 1433

Bushings
 gear 2117
 jig, materials for 941
 standard, for jigs 941–951
 steels for 456

Butt joint, riveted 1457–1462

Buttress threads 1817–1824
 allowances and tolerances 1821–1823
 ANSI Standard inch type 1818–1824
 basic dimensions 1817–1818
 British Standard 1825
 designations 1824
 diameter-pitch combinations 1817–1818
 miscellaneous types 1817–1824
 symbols and formulas 1820
 thread form 1818–1819
 wire method of measuring 1875–1877

Byte 2533

Byte, PLC 1229

B18.2.1 1492

B18.2.2 1492

B18.6.7M 1577

C

Cables, wire, breaking strength 336–341

CAD/CAM 1287–1297
 drawing exchange standards 1294–1296
 projections 1289
 rapid prototyping 1296
 standard lettering sizes 1294
 tips 1290

Cadmium
 bearing alloys 2240
 plating 1444
 vacuum coating 1451

Cage materials, anti-friction bearings 2254–2255

Calculation procedure 1137

Calculations
 strength of materials, sample 212

Caliper
 gear tooth 2018–2020, 2108–2111
 measurement of 2020
 vernier 669

Calorie, kilogram 2514, 2546

Cams and cam design 1098–1099, 2163–2188
 acceleration, velocity, and displacement
 formulas 2163–2167
 classes of cams and followers 2163–2164
 cylindrical cams 2185–2187
 design example 2181–2184
 displacement
 constant velocity 2165
 curves 2163–2167
 cycloidal 2166–2167
 diagrams 2163–2169
 harmonic 2165–2167
 parabolic 2165–2166
 synthesis of 2167–2169
 forces 2179–2184
 machining errors, effect on
 acceleration 2183–2184
 materials 2179–2186
 milling 2186–2188
 pressure angle 2171–2178
 profile determination 2168–2171
 radius of curvature 2178–2184
 rollers 2186–2187
 size determination 2172–2176
 stresses, contact 2179–2180, 2184
 threading cams, screw machine 1094–1098

Canned (fixed) cycles, NC 1258–1262

Cap screws 1496, 1599–1604
 button head 1604
 drill and counterbore sizes for 1601–1602
 fillister head 1600
 finished, hexagonal 1496
 flat head 1599, 1603

- Cap screws *(continued)*
- hexagon socket type 1601–1604
 - hexagonal 1496
 - metric 1521
 - round head 1600
 - spline socket type 1601–1604
 - tap drill sizes 1889–1907
- Capacitor 1319
- Capital recovery 28
- Carat 2518
- Carbide tools
- application of cutting fluids to 1111
 - boring 859–865
 - coated 980–981
 - cutting 738–740
 - grinding 937–940
 - insert holders 726, 732–738, 1281–1284
 - insert type 726, 730–738
 - materials for 747–757, 979–981
 - sharpening 937
 - standard blanks for 738–740
 - tips for boring tools 859–864
 - tips for turning tools 741–746
- Carbides and carbonitrides 747–752
- Carbon
- monoxide, specific gravity 371
 - steel castings 1333–1334
 - steels 403, 406
 - AISI-SAE designations 409–410
 - cold drawn 430–431
 - composition of, SAE 420
 - heat treatments 504
 - mechanical properties 432–436
 - numbering system 403, 405
 - quality variations 418
 - speeds for milling 1014–1019, 1022
 - speeds for turning 996–999
 - structure of 483
 - tool steel as a cutting tool material 978
 - unified numbering system 403, 405, 413
- Carbon dioxide
- solidification temperature 623
 - specific gravity 371
- Carbonaceous mixtures 498
- Carbon-graphite bearings 2242, 2245
- Carbonitrides and carbides 747–752
- Carbonitriding 417–418
- Carburizing 417, 479, 498
- gas 498
 - liquid 498
 - solid materials 498
 - steels for 422–423
 - temperatures 504–505
 - vacuum 499
- Cartesian coordinates 36
- Case hardening 416–418, 479, 498
- steel 497
- Cash flow 30–31
- discounted 30–31
- Cast iron *(continued)*
- alloy 1328–1329
 - bearings 2241
 - chilled 1328–1329
 - density 370
 - ductile 1332
 - gray 1328–1329
 - malleable 1330–1331
 - Meehanite 1328–1329
 - nodular 1332
 - speeds and feeds for
 - drilling, reaming, and threading 1037–1038
 - milling 1021–1022
 - turning 1002–1003
 - strength 476
 - white 1328–1329
- Cast roller chains 2421
- Cast steel 1332–1336
- strength 476, 1332–1335
- Casting processes
- aluminum alloys 1342–1343
 - die casting 1337–1344
 - ductile iron 1332
 - gravity die casting 1337–1338
 - gray iron 1336–1337
 - green-sand molding 1336–1337
 - investment casting 1345–1347
 - low pressure casting 1337–1338
 - permanent mold 1337–1338
 - shell-molding 1336–1337
 - squeeze casting 1337–1338
 - V-process 1336–1337
- Castings
- alloy steel 1332–1335
 - blast cleaning 1338
 - brass and bronze 525–532
 - bronze and brass for gears 2117–2119
 - carbon steel 1333–1334
 - cleaning methods 1338
 - ductile (nodular) iron 1332
 - finishing operations 1338
 - heat treatment 1338
 - heat-resisting 1328–1329
 - investment 1345
 - malleable iron 1330–1331
 - malleable iron, strength 476
 - manganese steel 1335
 - Meehanite 1328–1329
 - nodular cast iron 1332
 - nonferrous strength 477
 - removal of gates and risers 1338
 - shrinkage of 1339–1343
 - steel 1332–1336
 - steel, for gears 2063, 2113–2117
 - surface texture of 708
 - weight, obtained from pattern weight 1340
- Castle and slotted nuts 1493, 1500–1502, 1552, 1554
- Cathode 1319

- Cell, flexible manufacturing, NC 1235
- Celsius (Centigrade) and Fahrenheit temperatures 2514–2516
- Cement, strength of 478
- Cementation 479
- Cemented carbide tools 747–752
 - coated 750–752
 - grinding 937–940
 - materials for 979–981
 - speeds for drilling with 1030–1033, 1035–1041
 - speeds for milling with 1013–1022
 - speeds for turning with 996–1009
- Cementite 483
- Cements, pipe joints 2464–2466
- Center
 - distance, gear set 2010, 2012, 2080
 - drills reamers and machine countersinks 813
 - of oscillation 151
 - of percussion 151
- Center distance 1999
- Center distance, gearing 1999
- Center of gravity 136–142, 151
 - any four-sided figure 137
 - circle sector 138
 - circular arc 137
 - cone 140
 - cone, frustum 140
 - cylinder 139
 - cylinder, portion of 139
 - ellipse segment 138
 - ellipsoid, segment of 141
 - fillet 138
 - of two bodies 141
 - parabola, area of 139
 - paraboloid 141
 - part of circle ring 138
 - perimeter or area of parallelogram 136
 - pyramid 140
 - pyramid, frustum 140
 - spandrel 138
 - sphere, hollow 141
 - spherical sector 141
 - spherical segment 141
 - spherical surface 138
 - spheroid, segment of 141
 - trapezoid 137
 - triangle 136
 - wedge 140
- Centering tools
 - feeds for 1094–1095
 - length of point 925
- Centerless grinding 1183–1185
 - screw threads 1926–1927
 - troubles 1184–1185
- Centers, for arbors and reamers 813
- Centimeter-gram-second system of measurement 2520
- Centimeter-inch conversion tables 2533
- Centipoises 2201–2202, 2312–2313, 2319
- Centistokes 2201–2202, 2312–2313, 2319
- Central plane 1999
- Centralized lubrication systems 2313–2315
- Centralizing Acme threads 1802–1811, 1816
 - alternative series 1816
 - designation 1811
 - formulas for determining diameters 1804
 - limiting dimensions 1804–1807, 1811
 - major and minor diameter allowances and tolerances 1810
 - pitch diameter allowances 1808
 - thread data 1807
 - thread form 1794, 1803
- Centrifugal
 - clutches 2332
 - force 163–166
 - calculation 164
 - stresses in flywheels 178
- Ceramic cutting tool materials 752–755, 981
- Cermets 747
- Chain
 - cast roller 2421
 - close-link 355
 - crane and hoisting 351–360
 - detachable 2421
 - pintle 2421
- Chamfers and corner clearance, gearing 2135
- Change gears
 - helical gear hobbing 2080–2083
 - helical milling 1931
 - leads and angles for helical milling 1946–1947
 - relieving helical-fluted hobs 1916–1917
 - thread cutting, lathe 1912–1916
 - fractional ratios 1913–1914
 - fractional threads 1912
 - metric pitches 1912–1913
 - modifying the gearbox output 1913–1916
 - threads per inch with given combination 1912
- Channels
 - aluminum 2498
 - elements of 2494, 2498
 - moment of inertia 2494, 2498
 - radius of gyration 2494, 2498
 - section modulus 2494, 2498
 - steel 2494
 - structural 2494, 2498
 - weight per foot 2494, 2498
- Characteristic, logarithm 102, 104
- Charcoal, weight and volume 371
- Checking
 - Acme threads by three-wire method, table 1872
 - American standard threads by three-wire method, table 1866–1867
 - assembly 619
 - castings 619
 - dimensions 619
 - drawings 618–619

- Checking *(continued)*
- for strength 618
 - gear size 2094–2112
 - machined parts 620
 - radius of arc 690–693
 - Whitworth threads by three-wire method, table 1868
- Cheese head screws, British Standard 1591, 1595–1596, 1598
- Chemical
- treatment of metals 1440–1443
 - vapor deposition (CVD) 750
- Chilled cast iron 1330
- Chipbreakers 728
- grinding 939–940
- Chisels, cold steels for 456
- Chord
- length for given angle and radius 80–81
 - length for given number of divisions 955–958
- Chordal addendum 1999, 2018
- milled bevel gear teeth 2064
 - milled, full-depth gear teeth 2016–2017
- Chordal distance of bolt circle 78
- Chordal thickness 1999
- gear teeth 2015–2017, 2062
 - milled bevel gear teeth 2064
 - milled, full-depth gear teeth 2016–2017
 - OD is special 2018
 - OD is standard 2015
- Chrome 1445
- Chromium
- plating 1427
 - tool steels 458, 460, 462
- Chucking reamers 808–822
- expansion 814
 - rose 808, 822
- Chucks
- drill, tapers and threads for 919
 - hexagonal, for portable tools 1210
 - spindle, for portable tool grinders 1207
- Cincinnati milling machines, indexing movements 1986–1989
- Circles
- chords for dividing circumference of 955–958
 - dividing, on jig boring machine 959–970
 - enclosed within a circle 72–75
 - enclosed within a rectangle 77
 - geometry of 48–50
 - lengths of chords for dividing 955–958
 - packing
 - in circles 72–75
 - in circles and rectangles 72–77
 - in rectangles 77
 - programming in APT (NC) 1267–1270
 - segments 80–81
 - squares of equivalent areas 79
- Circular
- disk
 - radius of gyration 147
- Circular *(continued)*
- gear teeth 2006–2008
 - interpolation, NC 1254–1255
 - mil gage for wires 2517
 - pitch 1999, 2127
 - given center distance and ratio 2014
 - pitch gears, diameters of 2022
 - ring sector, area 64
 - ring, area 64
 - ring, thin flat 148
 - saws, arbors for 1203
 - sector segment 955–958
 - sector, area 63
 - segment, area 63
 - thickness 1999
 - milled bevel gear teeth 2064
 - outside diameter
 - has been enlarged 2015
 - has been reduced 2015
 - is standard 2014
- Circular arc
- enter of gravity 137
- Circular pitch 1999
- Circular pitch in gears 2022
- Circular thickness 1999
- Circumference, chords for dividing 955–958
- CL data, NC 1242
- Classical V-belts 2379–2386
- Clavarino's equation 271
- Cleaning castings 1338
- Clearance 1999
- angles
 - boring tools 859–864
 - milling cutters 800
 - punch and die 1301
 - reamers, tooth rest position 811
 - single-point tools 740–746
 - turning tools 740–746
 - drill sizes, machine screw 1900
 - for wrench 1510–1511
 - ANSI Standard 1532
 - British Standard 1903–1904
- Clevis pins 1648
- Closed-loop system 1233, 2468–2470
- Clutches 2329–2336
- centrifugal and free-wheeling 2332
 - cone 2330–2331
 - cutting with angular cutters 2334–2336
 - disk 2329
 - friction 2329–2330
 - friction coefficients 2330
 - magnetic 2331–2332
 - positive 2333–2334
 - power capacity of 2329
 - saw tooth 2335–2336
 - slipping 2332
 - wrapped spring 2332–2333
- CNC 1225–1226
- programming 1240–1280
- Coatings 1444–1451
- Coatings, conversion, of metals 1440–1443

- Cobalt 939
 alloy 981
 Cobaltchrom steel 508
 Coefficient of friction 190–191, 2045, 2330, 2341
 rolling resistance 191
 Coefficient of heat radiation 367
 Cold-form tapping 1904–1907
 Collets 971–973
 Colloidal suspension 1319
 Coloring metals 1440–1443
 Columns 261–267
 American Institute of Steel
 Construction 264–265, 267
 American Railway Engineering
 Association formulas 261
 eccentrically loaded 262
 Euler formula 261–263, 266–267
 J. B. Johnson formula 262, 266–267
 Rankine or Gordon formulas 261, 263
 steel pipe, allowable concentric
 loads 264–265
 Combination
 drill and tap 1909
 shanks for end mills 781
 Combinations of involute spline types 2138
 Combined stress 206
 normal stresses at right angles 206
 Combined stresses 207–210
 Compensation, insert radius, NC 1281–1284
 Complex conjugate 39
 Complex or imaginary numbers 38
 Composite, checking of gears 2042
 Compound
 angles 688–690
 indexing 1950–1956
 thread cutting, NC 1263
 Compression
 in beams 236, 256–257
 in columns 261–267
 of air 395–401
 springs 285–305
 Compressive properties
 ceramics 379
 definitions 196
 strength, values of 476, 478
 wood 375–376
 Computer numerical control, CNC 1225–1226
 programming 1240–1280
 Computer-aided (or-assisted)
 design (CAD) 1287–1297
 manufacturing (CAM) 1287
 Concave arbor-type milling cutters 790
 Concrete
 specific gravity and weight 370
 strength 478
 Conditional expressions, NC 1258
 Conductance, thermal 366
 Conductivity
 electrical, of metals 1323–1324
 Conductivity *(continued)*
 electrical, of plastics 580–581
 thermal 368–370, 379
 Cone
 center of gravity 140
 clutches 2330–2331
 frustum
 center of gravity 140
 polar moments of inertia 144
 radius of gyration 150
 frustum of 68
 polar moments of inertia 144
 radius of gyration 149
 Cone volume 68
 Conical pendulum 188–189
 Conjugate fractions 14–16
 Constructional steels 1150–1151
 Contact
 diameter 1999, 2028
 diameter, gearing 2028–2033
 ratio 1999, 2029
 face 1999
 factor 2044–2045
 total 1999
 ratio, gearing 2024–2029
 stress 1999, 2045
 stresses, cams 2184–2186
 Contact diameter 1999
 Contact ratio 1999
 Contact ratio factor 2044–2045
 Contact stress 1999
 Contents of tanks 58–59
 Continued fractions 13–14
 use of as conjugates 15–16
 Contour Milling 1994
 Contourmilling 1994
 Control, adaptive, NC 1233
 Convergents 13–16
 Conversational part programming,
 NC 1240–1241
 Conversion
 coating of metals 1440–1443
 cutting speed formulas 985
 tables
 angular measure 90, 92
 cutting speed and diameter to rpm 986,
 1174
 cutting speed formulas 1908–1909
 decimal equivalents of inch
 fractions 2519
 decimal multiples of SI units 2522
 foot-pounds into Btu 2553
 hardness 520–524
 horsepower into kilowatts 2553
 metric into English measure 2525–
 2550
 miscellaneous English units 2532
 oil viscosity unit 2201–2202, 2312–
 2313
 pounds-force into newtons 2550
 radians into degrees 90, 92

- Converting numbers to powers-of-ten notation 18
- Convex arbor-type milling cutters 790
- Coolants for
 - lapping 1202
 - machining
 - aluminum 1116
 - magnesium 1117–1118
 - tool sharpening 939–940
 - zinc alloys 1118
 - tapping 1889–1890, 1909
- Coordinate system, converting to another 36
- Coordinates, for jig boring 953–970
- Copolymer 569
- Copper
 - flat products, strength 477
 - lead bearings 2238–2241
 - linear expansion 368–369
 - plating 1445
 - silicon alloys 565
 - wire, strength 477
 - zinc-tin alloys, strength 478
- Copper and copper-base alloys
 - cast 525–532
 - classification 525
 - Copper-beryllium 565–566
 - die casting 1343
 - passivation 1441–1442
 - speeds, for drilling and reaming 1041
 - for turning and milling 1006
 - wrought 533–542
- Copper- and iron-base sintered bearings 2243–2245
- Copper Development Association 525–542
- Cordage Institute 353, 360
- Core drills 846–849
- Corner-rounding milling cutters 775, 790
- Corrosion-resisting alloys 425, 428, 525–566
 - castings 1335
- Cosecant 83
- Cosine 83
- Cosine law of 84
- Cotangent 83
- Cotter pins, standard sizes 1648, 1659, 1662
- Cotters 2354
- Coulomb shear theory (plastics) 584–585
- Counterbores 857–858
- Countersinks 813, 862
 - combined with drills 845
 - machine 813
- Countersunk head
 - rivets 1466, 1470–1472
 - British Standard 1464, 1472–1474
 - screws 1569–1571, 1574–1575, 1591–1599, 1603
 - British Standard 1591–1598
- Couples and Forces 120
- Couples of forces 121
- Couplings
 - double-cone 2326
- Couplings *(continued)*
 - fire-hose 1842–1845
 - flexible 2327
 - hose 1841–1843
 - interference fits 2326
 - knuckle joint 2328–2329
 - safety flange 2325
 - single keys used as fixed 2140, 2143
 - slipping 2332
 - universal 2327–2328
- CPVC plastics 380, 601, 2511
- Crane chain
 - hoisting 351–360
 - safe loads 352
 - strength 351–354
- Crane motors 2456–2457
- Crane, hooks 351–360
 - capacity of 357
 - dimensions 357
- Crater-resistant carbide tools
 - materials for 980
- Craters 1319
- Creep 524, 576–577
 - rupture 524, 576–577
- Critical
 - slenderness ratio 261–262
 - speeds 185–186
 - formulas for 185–186
 - of rotating bodies and shafts 185
 - speeds of rotating shafts 283
 - temperatures, heat treatment 479, 485
 - determining 486
- Crobalt alloy 981
- Croning shell mold process 1336–1337
- Crosby Group 356–359
- Cross recesses
 - for machine screws 1577
 - for self-tapping screws 1623
- Cross section lining, ANSI Standard for drawings 606, 608
- Crossed helical gears 1998
- Crowned
 - involute splines 2145
 - splines for large misalignments 2145
- Crowned involute splines 2145
- Crushing strength, wood 375
- Cryogenic treatment, steel 514–517
- Cube, volume 66
- Cubes of wire diameters 330
- Cubic
 - boron nitride (CBN) 982, 1002, 1004, 1008, 1018, 1021–1022, 1139–1140, 1157, 1166
 - grinding wheels 1157, 1166
 - conversions 2542
 - equations 33
 - measure 2517, 2542
- Cumulative fatigue damage 198
- Cupola malleable iron 1330–1331
- Curve, normal distribution 1216–1219
- Cutoff 701

- Cutoff or roughness sampling length 707
- Cutter
- checking relief and rake angles 801, 805
 - clearance angles 800–801, 806
 - compensation, NC 1251–1253, 1281–1284
 - grinding 798–806
 - location data (CL data) 1242
 - radial relief, eccentric type 801–805
 - rake angles 800–801
 - spline 799
 - tooth rest positions 806
 - wheels for sharpening milling cutters 798–800
- Cutter compensation, NC 1251–1253, 1281–1284
- location data, NC 1242
- Cutters
- angular, milling 777, 783, 796–799
 - bevel gear, formed types 2058–2061
 - boring-bar 859–864
 - box-tool 1095
 - fluting, for reamers 808–810
 - helical gear, formed type 2077–2079
 - internal gear 2047
 - milling 771–806
 - speeds and feeds for sharpening 800 - milling, steels for 452–456
 - roller chain sprocket 2439–2441
 - spur gear, formed type 2017–2021
 - T-slot 775
 - Woodruff keyseat 795
- Cutting
- abrasive 1204
 - electric arc 1428–1429
 - fluids 1106, 1108–1111
 - application of to carbides 1111
 - aqueous solutions 1107
 - broaching 1108–1109
 - carbides 1111
 - chlorinated oils 1107–1109
 - magnesium 1108–1109, 1111
 - mineral oil 1109
 - selection 1107–1109
 - soluble oils and compounds 1107
 - sulfurized oils 1107, 1109–1110
 - various alloys 1107–1109 - gas torch cutting 1428–1429
 - roller chain sprocket teeth 2437
 - time for turning, boring and facing 1044
 - wire rope 344
- Cutting bevel gear teeth 2053
- Cutting speeds and feeds 978, 1040–1046
- automatic screw machine 1095
 - bandsaw 1103–1105
 - broaching 1043
 - chip thickness 992–994
 - cutting speed calculations 1005
 - cutting tool materials 444–471, 747–757
 - CVD diamond tools 982
- Cutting speeds and feeds (*continued*)
- diamond tools 981–982
 - drilling and turning titanium and titanium alloys 1007
 - drilling superalloys 1008–1009
 - drilling, reaming, and threading 1012–1043
 - copper alloys 1041
 - feeds 1012
 - ferrous cast metals 1037–1038
 - glass 1034
 - light metals 1039
 - plain carbon and alloy steels 1030–1035
 - stainless steels 1036
 - tool steels 1035 - equivalent
 - chip thickness (ECT) 992–994
 - rpm for given cutting speed 986–990
 - rpm for given drill sizes and speed 986 - formulas for 985, 1005
 - honing 1196–1198
 - metal cutting saws 1044
 - milling 1009–1012
 - feeds for high-speed steel cutters 1023
 - ferrous cast metals 1021–1022
 - plain carbon and alloy steels 1014
 - slit and slot 1012–1013
 - stainless steels 1019–1020
 - superalloys 1008–1009
 - titanium and titanium alloys 1007
 - with cemented carbide cutters 1009–1012 - planing 1044
 - rpm for different speeds and diameters 987–990
 - shaping 1044
 - tapping 1012–1039, 1041–1043, 1959–1975
 - thread chasing 1041–1043
 - tool
 - angles 723–730
 - inserts 747–757, 1281–1284
 - life 982–983, 992–994
 - adjusting 755–757, 1004–1005, 1009, 1012, 1028 - materials related to 978 - tool steels 1000, 1018–1019, 1035
 - turning
 - copper alloys 1006
 - ferrous cast metals 1002–1003
 - hard-to-machine materials with CBN tools 1008–1009
 - light metals 1007–1008
 - plain carbon and alloy steels 996–999
 - stainless steels 1001
 - superalloys 1008–1009
 - titanium and titanium alloys 1007
 - tool steels 1000
 - unusual materials 1044
 - work materials 978

- Cutting tools 723–726
 angles 723–738, 1281–1284
 application codes, ISO 753
 carbide grade selection 747–757, 980–981
 carbon tool steels 978
 carbonitrides (cermets) 747–752, 981
 cast nonferrous alloy 981
 cemented carbides 747–757, 979–981
 ceramics 752–755, 981
 coated carbides 980
 coatings 750, 980
 compositions and properties 748–750
 crater-resistant carbides 980
 cubic boron nitride (CBN) 754–757, 982, 1140, 1157, 1166
 CVD diamond 982
 diamond 750–757, 981–982
 CVD 982
 polycrystalline 754–755, 981–982
 synthetic 755–757
 grades 752, 980–981
 high-speed steel 979
 inserts 1281–1284
 machining data 755–757
 materials 978–982
 sharpening 934–935
 single-point 723–738
 specifications, ISO 751–752
 titanium carbides 749–752, 980
 trouble-shooting checklist 983
 tungsten carbide 747, 979
 combined with other elements 749–750
 whisker-reinforced 754
- Cyanide
 bath for heating steel 487
 hardening 498
- Cyaniding 417–418, 480
- Cycloid 1999
 area 63
 curves, area enclosed by 58
- Cylinder
 center of gravity 139
 collapsing pressure 273–274
 hollow
 polar moment of inertia 144
 radius of gyration 149
 volume 68
 plates and shells 268–274
 polar moment of inertia 144
 portion of volume 67–68
 portion of, center of gravity 139
 radius of gyration 148
 strength to resist internal pressure 270–274
 working pressure vs. radius ratio 272
- Cylindrical coordinates 38
- Cylindrical grinding 1175–1183
 automation in 1178–1179
 basic process data 1178
- Cylindrical grinding *(continued)*
 high speed 1178–1179
 machines 1175
 operating data 1177
 selection of grinding wheels 1142, 1156–1157, 1166, 1176–1177
 traverse and plunge grinding 1175
 troubles 1179–1183
 workholding 1176
- Cylindrical tank, contents 58–59
- Cylindrical to rectangular coordinates 38
-
- ## D
- Data input, manual, NC 1240
- Datum referencing 610–611, 614
- Datum target points 616
- Datum targets 615
- Decalescence point in steel hardening 479, 485
- Decimal
 equivalents, fractions 2519
 multiples and submultiples of SI units 2522
 point programming, NC 1245
- Dedendum 1999
- Definitions
 gear terms 1998
 geometric dimensioning and tolerancing 610
 spline terms 2142
 surface texture 699
 surfaces of solid materials 697
- Deflection
 beams 236, 239, 241–242, 253–254
 calculating 206
 flat plates 268–270
 shaft, linear 280
 shaft, torsional 277–280
 springs
 compression and extension 302
 torsion 321–324
- Degrees, expressed in radians 90, 92
- Density 370
 air 394
 ceramics 379
 metals 368–370
 plastics materials 380
 powdered metals 383
 wood 376
- Department of Commerce 272–273
- Deposition rates (welding) 1367, 1375–1378, 1390–1391
- Depth of cut 982–983
- Depth of engagement 2127
- Derivatives of functions 34–35
- Detachable chains 2421
- Deviation, mean positional 1217
- Diameter of circle enclosing smaller circles 72–75

- Diameters for finished shafting 280
- Diametral
 - equivalent circular pitch and tooth proportions 2007–2008, 2091–2093
 - equivalent modules 2091–2093
 - pitch 1999
 - pitch knurls, (ANSI) Standard 1212–1215
 - pitch, gear teeth sizes 2002–2004
- Diamond
 - concentration 937–938
 - dust for lapping 1201
 - grinding wheels 1152–1169
 - laps and lapping 1201
 - tool materials 754–757, 981–982
 - truing 1158–1162
 - wheels 937–939, 1163–1169
 - composition 1166
 - designation symbols 1163–1166
 - diamond concentration 937–939
 - feeds and speeds 1169
 - grades, grit sizes 937–938
 - modifications 1166
 - operating guidelines for 1169
 - selection of 1168
 - shapes of standard 1163–1166
 - speeds and feeds 1169
 - terminology 1163
 - thread grinding 1923
- Die blocks, steels for 452–456
- Die casting 1337–1344
 - alloys used 1342
 - bearing metals 1344
 - design 1341–1342
 - dies 1343–1344
 - machining zinc alloy 1118
 - porosity 1341
- Die sinkers' files 1432
- Diemaker's reamers 797
- Dies and punches, steel for
 - drawing 1302–1307
 - hot-working 452–454, 456
- Dies and taps
 - combination drill and tap 1909
 - maximum pitches 1929–1930
 - selection of 1885–1887
 - square thread 883, 887–890
 - tap drill size 901, 1889–1908
 - Acme threads 901
 - formula 1900–1901
 - metric 1903
 - pipe 1907–1909
 - Unified 1889–1902
- Dies, sheet metal
 - angular clearance for 1302
 - bending allowances 1304–1310
 - blank diameters for drawing 1304–1307
 - blocks, steels for 452–454, 456
 - clearance between punch and die 1301
 - diameter reductions in drawing 1305
 - dies, sheet metal *(continued)*
 - heat-treatment, steels for 452–454
 - lubricants 1302
 - press speeds and pressures 1302–1304
 - punching pressures 1302–1304
 - rectangular drawing 1302–1304
 - shut height of press 1302–1304
 - steels for various classes of die parts 452–454, 456
 - steel rule 1315–1317
 - threading, maximum pitches 1929–1930
- Differential
 - indexing 1976–1985
 - pulley 135
- Dimensioning and tolerancing, geometric 606, 610–611
- DIN 867 2090
- Direct (or distributed) NC 1296
- Discounted cash flow 30–31
- Disk
 - circular, radius of gyration 147
 - clutches 2329
 - method of measuring tapers 682–683
 - springs 326
- Displacement in ball and roller bearings, allowance for axial 2264
- Distance across bolt circle 687
- Distributed numerical control (DNC) 1296
- Distribution curve, normal 1216
- Dividing
 - circles 959–970
 - head
 - angular position 796–799
 - indexing 1947–1993
 - numbers written in powers-of-ten notation 19
- DNC 1296
- DOD-P-16232-F 1450
- Dolly bars for riveting 1467
- Double angle milling cutters 777
- Double V-belts 2386–2394
- Double-cone clamping couplings 2326
- Dovetail slides, measuring 682–683
- Dowel pins 1648–1654
 - metric 1648–1650
- Drafting practices, ANSI Standard 606–611
- Draw-in bolt ends 923
- Drawing
 - ANSI Standard
 - drafting practices 606–611
 - lines 606
 - sheet sizes 606
 - surface texture symbols 704–708
 - welding 1394–1409
 - bisect angle 52
 - checking 618
 - circle around square 54
 - circle around triangle 53
 - circular arc 53
 - data for gear blanks 2033

- Drawing *(continued)*
- data for gears 2033–2036
 - data for involute splines 2139
 - divide line into equal parts 51
 - ellipse 54
 - equilateral triangle 52
 - helix 55
 - hexagon around circle 54
 - hyperbola 55
 - involute 55
 - metric dimensions on 708
 - parabola 55
 - parallel lines 52
 - perpendicular lines 51
 - sizes of sheets 606
 - square around circle 54
 - symbols
 - ANSI Standard 606–611
 - section lining 606
 - geometric 609
 - ISO 609
 - tangent to circle 53
 - triangle around circle 53
 - 45-degree angle 52
 - 60-degree angle 52
- Drawing data, splines 2140
- Drawing dies
- annealing drawn shells 1302
 - blank diameters 1304–1307
 - brass 1302
 - depth drawn in one operation 1305–1307
 - diameter reduction in one operation 1305–1307
 - rectangular 1302–1304
- Drawing, or tempering, steel 493–495
- Drawings
- checking
 - inspecting a new design 618
 - materials specified 618
 - method of making drawing 619
 - data for spur and helical gear 2036
 - metric dimensions on 710
 - scales of metric drawings 711
 - specifying spur and helical gear data on 2034
- Dressing grinding wheels 1158–1162
- Drill
- sizes for tapping Acme threads 901
 - sizes for wood screws 1456
- Drilling
- accuracy of drilled holes 856–858
 - automatic screw machine feeds and speeds 1095
 - cutting speeds for 1094
 - ferrous cast metals 1037–1038
 - light metals 1039
 - superalloys 1008–1009
 - titanium and titanium alloys 1007
 - tool steels 1035
 - difficulties 1034
- Drilling *(continued)*
- estimating thrust, torque, and power 1051–1055
 - feed rates for 1012
 - holes in glass 1034
 - holes, accuracy of 856–858
 - horsepower and thrust for 1051–1055
 - machine, shaftless motor type 2454
 - spade 865–871
- Drills
- accuracy of drilled holes 856–858
 - angle of cutting point 934–936
 - chucks, tapers 919
 - cobalt high-speed steel 857
 - combined drills and countersinks 845–847
 - core, taper shank 847
 - cutting speeds and equivalent rpm 986
 - definitions of terms 827
 - diameters of tap 1889–1903
 - drivers 848–850
 - for taper pin reamers 1655–1658
 - grinding 934–937
 - jobbers length 829–835
 - length of point 925
 - metric, British Standard 847–856
 - nomenclature 827
 - screw machine drills 829–840
 - sharpening 935–937
 - sizes for tapping 1889–1903
 - for Acme threads 901
 - spade 865–871
 - steels for 856–857
 - straight-shank drill sizes
 - core drills 849
 - letter 833–834
 - metric 829–839
 - number 829–833
 - straight-shank, taper-length, drill sizes
 - fractional 830–839
 - letter 833–834
 - metric 830–839
 - number 830–833
 - screw machine length 840
 - tangs for 839
 - tap and clearance hole sizes 1900
 - taper-shank core drills 846–849
 - taper-shank drill sizes
 - fractional inch 841–846
 - metric 841–846
 - twist 827–858
 - types 827
- Drives
- motors, NC 2471–2473
 - nose key 911–912
 - screws 1620–1621, 1635
 - square, for portable tools 1208
 - studs 1662
 - taper 910–911
- Driving slots and lugs for shell reamers and arbors 823

Drop-forging dies, steels for 452–456
 Drums, chain and wire rope 342–343, 360
 Dry measure 2518, 2523
 Dryseal pipe threads 1852–1855
 taps for 881
 Ductile
 cast iron 1332
 iron 476, 1332
 Duranickel, machining 1118
 Durometer tests 521
 Dynamic
 balance 167
 stresses 257–258
 Dynamic factor 2044–2045
 Dynamic viscosity coefficient for
 lubricants 2324
 Dynamometers 2338–2341
 Dyne 2520

E

Earth, weight of 370
 Eccentricity 2136
 Economic Tool-life 1073
 ECT
 grinding 1121
 ECT (equivalent chip thickness) 992–994
 EDG (electrical discharge grinding) 1319
 EDM 1318–1329
 dielectric filter 1319
 dielectric fluid 1319
 dielectric strength 1319
 discharge channel 1319
 dither 1319
 duty cycle 1319
 electrode growth 1319
 electrode wear 1319
 electro-forming 1319
 Farad 1319
 gap 1320
 gap current 1320
 gap voltage 1320
 heat-affected zone 1323–1324
 ion 1320
 ionization 1320
 low-wear 1320
 negative electrode 1320
 no-wear 1320
 overcut 1320
 overcut taper 1320
 plasma 1320
 plunge (sinker) method 1321–1328
 electrode materials 1324
 machine settings 1322
 making electrodes 1327
 metal removal rates 1323
 positive electrode 1320
 power parameters 1320
 process 1321
 quench 1320

EDM *(continued)*
 recast layer 1320
 secondary discharge 1320
 spark in 1320
 spark out 1320
 square wave 1321
 stroke 1321
 UV axis 1321
 white layer 1321
 wire EDM 1321
 wire guide 1321
 wire method 1318, 1328–1329
 wire speed 1321
 workpiece materials 1323–1324
 Effective
 dimensions, splines 2127, 2136
 length of bolt 1479
 vs. nominal interest rates 25
 Efficiency 2000
 influence of friction on 191
 machine tool 1048–1051
 spade drilling 870
 riveted joints 1459–1462
 Elastic
 limit 196
 modulus 196
 for various materials 196
 plastics 583
 region 196, 1483–1484
 tightening fasteners in 1477–1481
 Elastic properties of material 384
 Elasticity (rigidity)
 modulus of 196
 in shear (torsion) 196
 spring materials 326–329
 various materials 196
 Elasticity factor 2044–2045
 Elastohydrodynamic lubrication 2321
 Electric
 arc, cutting metals 1428–1429
 dielectric strength
 ceramics 379
 plastics 380
 socket and lamp base threads 1846
 Electrical relationships 2532
 Electrodes (welding)
 characteristics of standard types 1378–
 1382
 AWS E60XX 1379–1383
 AWS E70XX 1381–1383
 current to use with 1367–1386
 deposition rates 1364, 1367–1370, 1375–
 1377
 diameter to use 1363–1364, 1372, 1381,
 1383
 selecting GTAW tungsten type 1385–
 1387
 wire, feed rates 1367–1375
 Electropolishing 1447
 Elements, table of chemical 363
 Elevation reading displacements 1219